



▶ Key Feature

- Ultra-High Native Resolution
- Video Wall Function
- More Screen Units, Less Slim Frame
- Better Video Connection

▶ Specification

| | | | |
|-------------------------------|--|--|---|
| Display Panel | Screen Size | 57" | |
| | Active Display Area(mm) | 1251.4 x 703.9 | |
| | Number of Pixels | 1920 x 1080(WUXGA) | |
| | Aspect Ratio | 16:9 | |
| | Display Colors | 16.7 Mil | |
| | Brightness(cd/m ²) / (typ) | 600 | |
| | Contrast Ratio | 2000:1 | |
| | Response Time(ms, G to G) | 8 | |
| | Viewing Angle (H°/V°) | 178/ 178 | |
| | Bezel Size(U/ D/ L/ R)(mm) | 26.65/ 26.65/ 34.1/ 34.1 | |
| | Out Line Dimension(mm) | 1328 x 764 x 64.5 | |
| | Weight(kg) | 31.1 | |
| | Input voltage | 12 | |
| Life Time | 50,000h average | | |
| Resolution(Max) | Monitor | 1920 x 1080(67.5kHz/ 60Hz) | |
| | DTV | 1080p(Multi Screen: 1080p) | |
| Connectivity & Control | Input | PC Analog(RGB, D-Sub) | 1 |
| | | HDMI | 1 |
| | | Composite(BNC) | 1 |
| | | Component(BNC_ Y/Pb/Pr) | 1 |
| | | PC Audio | 1 |
| | | Component Audio | 1 |
| | | Composite Audio | 1 |
| | | RS232C | 1 |
| | | Output | PC Analog(RGB, D-Sub) |
| | DVI(Connected type HDMI) | | 1 |
| | Component(BNC) | | 1 |
| | RS-232C | | 1 |
| | | Speaker(Ready) | 1 |
| | Multi-Screen Function(Loop) | HDMI, PC Analog(RGB, D-Sub), Component(BNC), Composite(BNC) | |
| | OSD Language | 10 Lang | |
| | Power Requirement | Input Voltage | 100 ~ 240VAC |
| | | Consumption On/ Working(typ)(w) | 460 |
| | Auto Cooling System | Yes(2EA) | |
| | Tempered Glass | Option | |
| Mechanical | Dimension(mm) | Set(W x H x L)(mm) | 1332.4 x 768.4 x 130.7 |
| | | Bezel Size(U/ D/ L/ R)(mm) | 31/ 31/ 39/ 39 |
| | | Packed(W x D x H)(mm) | - |
| | Weight(kg) (With out Glass) | Set Weight(kg) | 77.8 kg |
| | | Packed Weight(kg) | 84.8 kg |
| | Accessories | | Power cord, Manual, D-sub,HDMI Cable, Remocon |
| Other Features | | Auto cooling system, Auto power control (On& Off timer) | |
| Wall Mounting Hole(W X H mm) | | 700 x 374 | |